



GLORystAR

## ULTRON Windows Touchscreen Computer i3



**Capacitive Touch**



**Windows**



**Durable Built to Last**

### Overview

Ultron Windows Tablet Series is designed to be placed individually as an all-in-one kiosk. There are VESA mounting holes at the back for easy installations.

Available in 10.1", 15.6" and 21.5" widescreen

-----  
The most common operating system

-----  
Easy deployments with various VESA mounting

# Specification

i3 - 1215U				
	Model	ULT101 Part#1215U	ULT156 Part#1215U	ULT215 Part#1215U
Screen Size	Size	10"	15.6"	21.5"
Panel Info	Resolution	1280 x 800	1920 x 1080	1920 x 1080
	Panel Brightness	500cd/m <sup>2</sup>	250cdm <sup>2</sup>	500cd/m <sup>2</sup>
	Brightness	425cd/m <sup>2</sup> with touch Screen	TBD	425cd/m <sup>2</sup> with touch Screen
	Contrast	800:1	800:1	1000:1
	Aspect Ratio	16:10	16:9	16:9
	Active Display Area	216.96 x 135.6 mm	344.16 x 193.59 mm	476.06 x 267.786 mm
	Viewing Angle	H:170°/ V: 170°	H:170°/ V: 170°	H:178°/ V: 178°
	Response time	30ms	25ms	20ms
Touch Data	Touch Tech	G+G 10 point cap touch		
	Hardness Of Surface	≥ 6H		
	Touch method	Finger touch , Capacitive stylus		
	Transparency	≥86%	≥85%	
	Response Time	TBD	< 5ms	< 5ms
	Touch Glass Thickness	2.9mm	2.05mm	2.95mm
CPU & System	CPU	i3-1215U		
	P-core Max Turbo Frequency	4.4GHz		
	E-core Max Turbo Frequency	3.3GHz		
	Core	6		
	Thread	8		
	CPU Cache	10MB		
	BIOS	AMI UEFI BIOS		
RAM	RAM	8GB , Dual Channel SO-DIMM DDR4 (Max 64GB)		
ROM	Storages	256GB, M.2 for NVME 2280 SSD		
Software	OS	Windows 11 64 bit, Linux 64 bit		
Display	GPU Chipset	Intel Iris® Xe Graphics eligible/UHD Graphics depends on CPU		
	Displayport	N/A		
Audio	Speaker	10 inch: 2W x 2 15 and 21 inch: 2W x 2		
Ethernet	Connector	2 x RJ45		
	Wake on Lan	Yes		
	WIFI/ Bluetooth	802.11a/b/g/n/ac/ax(PreStandard) , Bluetooth 5.0 (Dual antenna)		
Storage	Slot	M.2 for NVME 2280 SSD		
General	Material & Color	Metal Housing with Black Matte Paint		
	Chassis	N/A		
	Front	N/A		
	Back	N/A		
	Camera	2 MP		
	4G (Optional)	4G and WIFI function Choose one of the two (The 10.1-inch structure does not have 4G function)		
	Metal Button	1×Power button; 1×Reset button (1×Power button for 10 inch)		
Rear Panel I/O	USB 3.0	4xUSB 3.2		
	Audio	Line-out x1, Mic-in x1		
	LAN	1 x (1000Mbps) ; 1 x (2500Mbps)		
Insider PCBA	M.2	1×for NVME 2280 SSD		
	SATA3.0	1		
	COM	6 x RS232(default) or 5*RS232+1*RS485(COM1) (inside PCBA)		
	USB 2.0	4 x USB2.0 header (inside PCBA)		
	I/O	8 x GPIO (inside PCBA)		
Power	Standard Port	1 x 12V DC-IN		
Hardware Monitor	Hardware Monitor	CPU system temperature; onboard voltage; Watchdog; and auto power on		
	Included in Box	Ultron tablet, Power Adaptor, Power cable		
	Consumption	55W (MAX)	60W (MAX)	65W (MAX)
	Power Adaptor	12V 7.5A	12V 7.5A	12V 7.5A
	Operating Environment	Working Temperature: 0-45 degree celsius		
Mounting	Language	Multi language		
	VESA	VESA 75 for 10 inch, VESA 100 for 15.6 and 21.5 inch		
Dimensions	Size ( WxDxH)	266.36 x 185 x 43.7mm	393.27 x 250.27 x 44mm	530.5 x 322 x 44mm
	Product Weight	1.95Kg	3.3Kg	6Kg
	Gift Box Size	396 x 241 x 86 mm	443 x 115 x 303 mm	583 x 115 x 382mm
	Master Carton Size	506 x 410 x 288mm	464 x 365 x 327mm	604 x 248 x 406mm
	Master Carton Weight	16Kg	12.3Kg	15.3Kg
	Units per Master Carton	6pcs	3pcs	2pcs

## Peripheral Options

1D Barcode Newland	NEBAI701 PART#N002
2D Barcode Honeywell	NEBAI702 PART#H002
2D Barcode Zebra	NEBAI702 PART#Z002
Elatec RFID Reader Metal Housing	NEBAI703 PART#E002
Windows 10 IoT License	ULT Part# WIN KEY
Windows 11 IoT Enterprise LTSC	ULT Part# WIN KEY
256GB SSD Upgrade	X000103
4G (LTE) Module	JAF-009

## Mounting Options

Wall Mount	WM015012S
Desk Mount	FIX-027 (Foldable base bracket)
	FIX-028 (Adjustable Desk Mount)
	FIX-030 (Foldable base bracket)

## CONTACT US

United States	Hong Kong	ShenZhen
101 Hudson St., 21st Floor Jersey City, NJ 07302 <a href="tel:6262285927">626 228 5927</a>	Flat D, 5/F, Excelsior Building, 364 Nathan Road, Kowloon, Hong Kong <a href="tel:85223762803">852 23762803</a>	Bldg. 9, 4/F Zhong Yuntai Technology Industrial Park, Tangtou No.1 Road, Shiyan Street, Baoan, ShenZhen, PRC <a href="tel:8675526001808">86 755 2600 1808</a>

To find out more about our extensive range of Glor Star solutions, go to [www.glorystargroup.com](http://www.glorystargroup.com), or call the office nearest you. For more information, please contact us at [sales@glorystargroup.com](mailto:sales@glorystargroup.com). Glory Star reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Glory Star, the Glory Star logo, STAR CONTROL and STAROS are either trademarks or registered trademarks of Glory StarGroup Limited. All other trademarks are the property of their respective owners.