




# NEBULA *GLOW* 10"



**Capacitive Touch**



**Optional POE**



**With LED Lights**

## Overview

Nebula Glow - our 10-inch all-in-one touch screen device is perfect for meeting rooms, casinos, and any other space that requires a device with a visually striking design. With its high definition LCD panel and full viewing angle, the Nebula Glow delivers stunning visuals that are sure to capture your attention. The device also features a programmable LED light rim that can be customized to suit your needs, making it both functional and aesthetically pleasing. It also comes with POE (Power over Ethernet) enabled, allowing for easy installation and management. With the STAROS kiosk lockdown application and Star Control remote management system, the Nebula Glow is able to be remotely controlled. Finally, the capacitive touch screen technology ensures that the device is responsive and easy to use.

Available in 10", widescreen with selectable high-performance CPUs and IPS capacitive touchscreens

Choice of Wi-Fi / Ethernet

Optimize deployments with cloud-based configuration, monitoring and scheduling

Modern design with flexible mounting in portrait, landscape and table-top orientation

	Name	Nebula Glow Lite	Nebula Glow	Nebula Glow Plus
	Model	ALU100 Part#133/ GLOW	ALU100 Part#568/GLOW	ALU100 Part#399/GLOW
Screen Size	Size	10"	10"	10"
Panel Info	Resolution	1280x 800	1280x 800	1280x 800
	Brightness	250cdm2	450cdm2	450cdm2
	Contrast	1000:1	800:1	800:1
	Aspect Ratio	16:10	16:10	16:10
	Active Display Area	216.576 x 135.36mm	216.96 x 135.6mm	216.96 x 135.6mm
	Viewing Angle	85°/85°/85°/85°	85°/85°/85°/85°	85°/85°/85°/85°
	Response time	35ms	30ms	30ms
Touch Data	Touch Tech	G+G 10 point cap touch	G+G 10 point cap touch	G+G 10 point cap touch
	Hardness Of Surface	≥ 6H		
	Touch method	Finger touch , Capacitive stylus		
	Transparency	≥85%		
	Response Time	10us		
	Touch Glass Thickness	2.55mm		
Hardware & OS	Bonded Panel	Yes		
	CPU	A133 Quad-core 64-bit Cortex-A53 up to 1.5GHz	RK3568 Quad-core Cortex-A55 up to 2.0GHz	RK3399 Dual-core Cortex-A72 up to 1.8GHz Quad-core Cortex-A53 up to 1.4GHz
	RAM	2GB LPDDR4	4GB DDR4	4GB LPDDR4
	ROM	16GB eMMC Flash	32GB eMMC Flash	32GB eMMC Flash
	OS	Android 11	Android 12	Android 12
Software	STAROS	· Kiosk lockdown	· App Lockdown · Set timer to turn device on and off	· Hide control buttons
	STARCONTROL	· Manage device remotely	· Control power on/off · Upload video to device	· Manage apps remotely
	STARTOOL	Tool for developers to control device and Open API and controlling lights		
Video/ Image	Video Format	MOV, FLV, MP4, MKV, MPG, MPEG, etc		
	Audio Format	AAC, AMR, FLAC, M4A, M4R, MP2, MP3, OGG, WAV, WMA, etc		
	Image Format	JPEG, BMP, PNG,GIF, etc.		
Audio	Speaker	2W x 2		
Communciation	Bluetooth	BT 5.0		
	Camera	2MP		
	Noise Cancellation	N/A	Noise Canceling	Noise Canceling
WIFI	WIFI	802.11 a/b/g/n/ac 2.4GHz and 5GHz (Dual antenna)	802.11 a/b/g/n/ac 2.4GHz and 5GHz (Three antenna)	802.11 a/b/g/n/ac 2.4GHz & 5GHz (Three antenna)
	Ethernet	10/100 LAN	10/100/1000 LAN	10/100/1000 LAN
General	Color	Grey+Black		
	Chasis	Plastic		
	Plastic materials	"Flame retardant, TBBA" (LED light frame Non-flame retardant material)		
	I/O	RJ45x1 ,TFslotx1, TYPECx1(only OTG upgrade) ,3.5mm audio x1, DCx1 , type-c(USB2.0)x1	RJ45x1, USB2.0x1, TFslotx1, USB3.0x1, TYPECx1, 3.5mm audio x1, MICx2, type-c(USB2.0)x1, 1×UART; 2×GPIO; 1×Wiegand; 1×VCC-5V	RJ45x1, USB2.0x1, TFslotx1, USB3.0x1, TYPECx1, 3.5mm audio x1, 1×UART; 2×GPIO; 1×Wiegand; 1×VCC-5V
	POE	Yes IEEE802.3at (Choose either Power In or POE but not both at the same time)		
	Included in Box	Nebula Tablet, Power Adaptor, Power cable		
	Sensors	G- sensor , Ambient and Proximity sensor		
	Consumption	14.4W		
	Power Input	DC 12V 2A		
	Operating Environment	Working Temperature: 0-45 degree celsius		
	Language	Multi language		
Lights	Light Control	RGB LED		
Mounting	VESA	VESA 75		
	Certification	CE, FCC, UKCA		
Dimensions	Dimensions ( LxWXH)	267.05×185.69×28.85mm		
	Weight	1.1 K g		
	Box size / each pc (LxWXH)	385 x 222 x 65 mm		
	Master Box size ( LxWXH)	470 x 400 x 355 mm		
	Master Box Weight	15.2Kg		
Pieces/ Carton	10 PCS			

## Mounting Options

Shelf Mount	FIX-014 (Foldable Mount with Magnet at one side )
Wall Mount	WM015012S
Desk Mount	FIX-028 ( Adjustable Desk Mount)

## CONTACT US

United States	Hong Kong	ShenZhen
101 Hudson St., 21st Floor Jersey City, NJ 07302 USA <b>626 228 5927</b>	Flat D, 5/F, Excelsior Building, 364 Nathan Road, Kowloon, Hong Kong <b>852 23762803</b>	Bldg. 9, 4/F Zhong Yuntai Technology Industrial Park, Tangtou No.1 Road, Shiyan Street, Baoan, ShenZhen, PRC <b>86 755 2600 1808</b>

To find out more about our extensive range of Glory Star solutions, go to [www.glorystargroup.com](http://www.glorystargroup.com), or call the office nearest you. For more information, please contact us at [sales@glorystargroup.com](mailto:sales@glorystargroup.com). Glory Star reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Glory Star, the Glory Star logo, STAR CONTROL and STAROS are either trademarks or registered trademarks of Glory Star Group Limited. All other trademarks are the property of their respective owners.